

WALL LIGHTS SPECIFICATION SHEET



**COLLINGWOOD
LIGHTING**

01604 495 151
collingwoodlighting.com

/collingwoodlighting

/collingwoodlighting

collingwoodled

WL070

Silver straight to mains, high output LED wall light

FEATURES

IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	No
Dimmable	No
Input	220-240V 50/60Hz
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium
Weight	0.9kg
Maximum ambient temperature	40°C
Electric Class [1, 2, 3]	1

GUARANTEE / WARRANTY

7 year extended warranty available

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution.

Bi-directional, straight to mains wall light, perfect for framing entrances and illuminating columns

Anodised Aluminium is both sleek and durability

Long lifetime of 70,000hrs

7 year warranty

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
WL070SNBM27	Silver	5.1W	2700K	12°	510 / 255	100	3147 / 1573
WL070SNBM30	Silver	5.1W	3000K	12°	550 / 275	108	3394 / 1697
WL070SNBM40	Silver	5.1W	4000K	12°	560 / 280	110	3455 / 1727
WL070BNBM27	Black	5.1W	2700K	12°	510 / 255	100	3147 / 1573
WL070BNBM30	Black	5.1W	3000K	12°	550 / 275	108	3394 / 1697
WL070BNBM40	Black	5.1W	4000K	12°	560 / 280	110	3455 / 1727
WL070CNBM27	Copper	5.1W	2700K	12°	510 / 255	100	3147 / 1573
WL070ZNBM27	Bronze	5.1W	2700K	12°	510 / 255	100	3147 / 1573
WL070ZNBM30	Bronze	5.1W	3000K	12°	550 / 275	108	3394 / 1697
WL070ZNBM40	Bronze	5.1W	4000K	12°	560 / 280	110	3455 / 1727

WIRING INFORMATION


Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVER

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

ACCESSORIES

N/A	No accessories required
-----	-------------------------



Beam angle:

